



Antenna Mast MA4000-DG

Antenna height	1.0 to 4.0 m
Total mast height	max. 4.6 m
Material	PVC + fibre glass, weatherproof
Mast cross-section	100 mm x 100 mm
Base L x W	1080 mm x 1080 mm
Antenna weight	max. 10 kg (15 kg available)
Positioning accuracy	better +/- 1 cm
Polarisation	0°...360° (1° steps)
Positioning time 0°...360°	approx. 10 sec.
Positioning accuracy	better +/- 1°
Antenna support drive	2 kevlar toothed belts (metal free)
Motor	electronic EC motor 150W
Control cable	fibre optic cable, POF type (standard)
Drive unit	shielded and radio interference suppressed 20dB under Class B
Temperature range	10°C...40°C
Input current	max. 2,2 A
Operating Voltage	115V / 230 V AC (50/60 Hz)

The MA4000-DG antenna mast is suitable for use in either open areas or in electromagnetic absorption chambers. Guy wires and anchoring pins are available for antenna installation in open areas. Metal parts are located only in the base plate and the drive mechanism (max. 0,3 m above ground level).

Adapters for all commercially available antennas are available. Special designs are available on request. All antennas during polarisation rotate around their axis so as to eliminate any elevation errors.

The **IEEE 488 (GPIB)** bus, when operated with the **CO2000** Controller, or **IEEE 488 (GPIB) & TCP/IP (LAN)** interface, when operated by [CO3000](#) Controller provides an additional control option for all functions.